

Product datasheet

Specifications



Auxiliary contact block, Easy TeSys Power, 1NO+1NC, mounted on left hand side

GZ1AN11

Main

Range of product	Easy TeSys Power
Range	Easy TeSys
Product or component type	Auxiliary contact block
Device short name	GZ1AN
Connections - terminals	Screw clamp terminals 1 cable(s) 1...2.5 mm ² solid Screw clamp terminals 2 cable(s) 1...2.5 mm ² solid Screw clamp terminals 1 cable(s) 0.75...2.5 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.75...2.5 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.75...1.5 mm ² flexible with cable end Screw clamp terminals 1 cable(s) 0.75...1.5 mm ² flexible with cable end

Complementary

Range compatibility	EasyPact EasyPact TVS GZ1E circuit breaker
Mounting location	Left side
Auxiliary contacts operation	Instantaneous 1 NO + 1 NC
Pole contact composition	1 NO + 1 NC
[Ui] rated insulation voltage	690 V conforming to IEC 60947-1
[Ue] rated operational voltage	48...690 V AC 24...240 V DC
[Ith] conventional free air thermal current	6 A
Protection type	GG fuse 10 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	300 VA at 48 V AC-15 - electrical durability: 70000 cycles 400 VA at 690 V AC-15 - electrical durability: 70000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 70000 cycles 500 VA at 500 V AC-15 - electrical durability: 70000 cycles 650 VA at 440 V AC-15 - electrical durability: 70000 cycles 720 VA at 230...240 V AC-15 - electrical durability: 70000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 70000 cycles
Rated operational power in W	120 W at 240 V DC-13 - electrical durability: 70000 cycles 140 W at 110 V DC-13 - electrical durability: 70000 cycles 140 W at 24 V DC-13 - electrical durability: 70000 cycles 180 W at 60 V DC-13 - electrical durability: 70000 cycles 240 W at 48 V DC-13 - electrical durability: 70000 cycles
Height	89 mm
Width	9.3 mm
Depth	66 mm

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net weight	0.05 kg
------------	---------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	1.500 cm
------------------	----------

Package 1 Width	7.000 cm
-----------------	----------

Package 1 Length	9.000 cm
------------------	----------

Package 1 Weight	44.000 g
------------------	----------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Height	9.500 cm
------------------	----------

Package 2 Width	9.800 cm
-----------------	----------

Package 2 Length	15.200 cm
------------------	-----------

Package 2 Weight	489.000 g
------------------	-----------

Unit Type of Package 3	S02
------------------------	-----

Number of Units in Package 3	60
------------------------------	----

Package 3 Height	15.000 cm
------------------	-----------

Package 3 Width	30.000 cm
-----------------	-----------

Package 3 Length	40.000 cm
------------------	-----------

Package 3 Weight	3.223 kg
------------------	----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
---	---

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Compliant
-----------------------------------	-----------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No
