

Product datasheet

Specifications



mini Pragma recessed enclosure - 3 x 12 modules - smoked door

MIP22312S

Main

Range	Resi9
product name	Resi9 MP
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	12
Nb of horizontal rows	3
Type of door	Smoked
Width	Wall: 270 mm Outside: 294 mm
Height	Wall: 478 mm Outside: 502 mm
Depth	Outside : 18 mm Wall : 80 mm Total : 98 mm

Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	36
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Mounting plate description	Without mounting plate
cable entry	Pre-cutted holes
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth (screwed) with 20 outgoers 1 neutral (screwed) with 20 outgoers
Distribution block outgoers	2 x 16 mm ² for earth 2 x 16 mm ² for neutral 9 x 10 mm ² for earth 9 x 10 mm ² for neutral 9 x 6 mm ² for earth 9 x 6 mm ² for neutral
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal depth	76 mm
Colour	Front face: white (RAL 9003) Door: smoked (RAL 9003)

Market segment	Residential Small commercial
----------------	---------------------------------

Environment

Standards	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
Quality labels	IMQ
Fire resistance	Door: 650 °C Back part: 650 °C Front face: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	29.500 cm
Package 1 Length	50.000 cm
Package 1 Weight	1.931 kg
Unit Type of Package 2	S04
Number of Units in Package 2	4
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	8.608 kg
Unit Type of Package 3	P12
Number of Units in Package 3	64
Package 3 Height	121.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	149.728 kg

Contractual warranty

Warranty	12 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 56

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Packaging

Minimum percentage of recycled plastic content 40

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number 5305d5d6-3783-4b3d-abd0-61fa4a6023d7

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Circularity Profile No need of specific recycling operations

Take-back No

Image of product / Alternate images

Alternative

Resi9 MP

Flush mounting enclosures

Base with pre-holes

- Clamping for hollow partition
- Carton protection for installation in


DIN rails

- 1 to 3 DIN rails fixed asymmetrically allow to have more space on entry cable side


Earth terminal block

- Clipped with screw or quick connection


Security combined with designed doors:
Reversible doors open to 140°, after which it can be removed, without breaking.



Smoked translucent



White (polystyrene)



Smoked transparent

Options

- Marker light: ensures that the electrical functions can be accessed in the event of a general power supply failure
- IK0-IP40
- Keylock

Resi9 MP - Dimensions

Flush mounting enclosures - from 4 to 36 modules

4, 6, 8, 12, 18 modules

